

FEUR PROFESSIONAL POWER AMPLIFIER



Model	FU-TRA3000	FU-TRA5000	FU-TRA7000	FU-TRA9000	FU-TRA11000
Stereo Power 8	2 X 800	2 X 1200	2 X 1500	2 X 2000	2 X 2600
Stereo Power 4	2 X 1000	2 X 1500	2 X 2100	2 X 2800	2 X 3100
BLT 8	1500W	2500W	3500W	4500W	6250W
BLT 4	3000W	5000W	7000W	9000W	11000W
THD+N	<0.03 % @ 8 Ω 1 KHz				
G Weight	20KG	24KG	26KG	40KG	42KG
Dimension	500x485x88 (2U)	500x485x88 (2U)	500x485x88 (2U)	515x485x133 (3U)	515x485x133 (3U)
S/N Ratio	>95dB	>95dB	>93dB	>93dB	>93dB
Slew Ratio	40V/μs	40V/μs	35V/μs	35V/μs	35V/μs
Damping Factor	>400	>400	>300	>300	>300
Output Circuitry	Class H				
Crosstalk	> 70dB @ 8 Ω1 KHz				
Input Impedance	0K (Balance) / 10K (Unbalance)				
Input Sensitivity	0.775V/1.0/1.4V				